

## UF-20TB/5

Order No. 0257230

### UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-18 dB to +12 dB)
- Lock function
- 5-level display for indicating battery status and low battery alert, backlit LCD

Model	UF-20TB/5
Description	pocket transmitter
Carrier frequency range	530-605 MHz
Audio frequency range	50-18,000 Hz
Operating time	> 20 h
Transmitting power	10/50 mW
Power supply transmitter	2 x batt. AA size (not supplied)
Dimensions transmitter	62 x 170 x 23 mm
Weight transmitter	90 g
Connections transmitter	4-pole mini XLR

- Switchable transmitting power

### There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



## CH-8

Order No. 0259410

### Transport case with integrated charging function, for transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5 and RU-G3TB/5.

- For simultaneously charging rech. batteries of 8 devices
- Average charging time, depending on capacity and condition of rechargeable batteries used: approx. 3 hours
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge
- Power is provided via supplied power supply
- Dimensions: 357 x 294 x 433 mm

Supplied w/o devices.

Model	CH-8
Description	transport case with integrated charging function
Colour	black
Suitable for	transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5, RU-G3TB/5
Power supply	via encl. power supply
Dimensions	357 x 294 x 433 mm
Weight	11.6 kg



## CH-2

Order No. 0257240

### Charging station, for transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5 and RU-G3TB/5.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 3 hours
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection

Model	CH-2
Description	charging station
Colour	black
Suitable for	transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5, RU-G3TB/5
Power supply	via enclosed power supply
Dimensions	165 x 72 x 99 mm
Weight	315 g

- Protection against overload, short-circuit and deep discharge
- Power is provided via enclosed power supply
- Dimensions: 165 x 72 x 99 mm



## MA-935

Order No. 0236850

### Adapter ring

- For mounting dynamic microphone cartridges from Sennheiser to hand-held UHF PLL transmitters JSS-20/5 and JSS-4B/5
- Aluminium version
- Screw thread



## RTF-UF20

Order No. 0236880

PAAR  
PAIR

### BNC antenna cable set

- For mounting antennas to the front panel of the UHF PLL wideband receiver UF-20R/5 or R-4/5
- 2 x 60 cm antenna cable with BNC plug and BNC inline jack

