

**WA-35**

Order No. 0172940

**Portable MP3 FM amplifier system with wireless microphone**

- Compact and ultra-light class D amplifier system (total weight: 1.75 kg)
- Power capability of 25 W in battery operation (integrated 14.8 V rech. LiPo battery) and 35 W with power supply
- Ideally suited for outdoor applications due to splash-proof housing, stainless steel screws, impregnated full range speaker with dual cone and push-on silicone cover for the control unit
- MP3 reproduction via USB interface and SD card slot
- FM radio with 20 station presets
- Wireless 16-channel microphone system in the licence-free range 863-865 MHz (1 x 1.5 V battery, AA size, not supplied)
- Sound adjustment
- Connection facility for a cable-connected microphone
- Alarm siren: 2-tone and wailing sound

Model	WA-35
Rated power (P <sub>RMS</sub> )	25 W (rech. batt.), 35 W (mains)
Peak output power	60 W
Carrier frequency	863-865 MHz
Power supply	14.8 V rech. LiPo battery, via power supply
Dimensions	146 x 179 x 223 mm
Weight	1.75 kg
Connections	1 x 6.3 mm jack (mic), 1 x USB

- LED lamp with continuous light, automatic SOS light and automatic flashing light
- Charging status indication
- Deep discharge protection
- 9 mm (3/8") stand sleeve
- Integrated recessed carrying handle
- Robust carrying strap with integrated microphone bag

**Licence-free in the EU.****HP-565**

Order No. 0221300

**Professional studio headphones**

- Excellent sound quality and a rich bass reproduction
- Semi-open system, over-ear
- Padded ear cushions and headband, comfortable to wear
- 3 m cable with single-sided cable inlet
- 3.5 mm plug with 6.3 mm adapter

Model	HP-565
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	500 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	104 dB/mW
Cable	3 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	350 g

**HP-535**

Order No. 0220790

**Professional studio monitor headphones**

- Excellent sound quality, very comfortable to wear
- Semi-open system, over-ear
- Padded ear cushions and headrest
- 2 m cable with single-sided cable inlet
- 3.5 mm plug with 6.3 mm adapter

Model	HP-535
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	1 W
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	64 Ω
Headphone sensitivity	104 dB/mW
Cable	2 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	380 g

**HPM-535**

Order No. 0220210

**Professional stereo headphones with electret boom microphone**

- Excellent sound characteristics, comfortable to wear
- Semi-open system, over-ear
- Compatible with sound cards
- Ideally suited for gaming
- Adjustable microphone boom
- Padded ear cushions and headband
- 2 m cable with single-sided cable inlet and 3.5 mm plugs

Model	HPM-535
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	1,000 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	64 Ω
Headphone sensitivity	104 dB/mW
Transmission range, mic.	100-15,000 Hz
Nominal impedance, microphone	680 Ω
Microphone system	electret
Microphone sensitivity	6.3 mV/Pa/1 kHz
Power supply	= 1.5-10 V
Cable	2 m, single-sided cable inlet
Plug	2 x 3.5 mm plug, gold-plated
Weight w/o cable	308 g

