

WSA-24R

Order No. 0257140

Wireless stereo receiver, 2.4 GHz, for audio streaming.

- Matching the transmitter WSA-24T
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level output via 6.3 mm jacks L/R
- Plastic housing
- Power is provided via enclosed plug-in power supply

Model	WSA-24R
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
S/N ratio	-
Transmitting power	-
Power supply	via encl. power supply
Dimensions	116 x 35 x 86 mm
Weight	118 g
Connections	Outputs: 1 x 6.3 mm stereo jack L/R, analogue



WSA-24T

Order No. 0257150

Wireless stereo transmitter, 2.4 GHz, for audio streaming.

- Matching the receiver WSA-24R
- Stereo/mono selector switch
- LED for indicating status and peak
- Interference-free operation due to FHSS technology (Frequency Hopping Spread Spectrum)
- Analogue line level input via 6.3 mm jacks L/R and 3-pole XLR L/R

Model	WSA-24T
Frequency range	20-20,000 Hz
THD	< 0.3%
Channel separation	≥ 90 dB
S/N ratio	-
Transmitting power	-
Operating range	> 30 m, without any obstacles
Power supply	via encl. power supply
Dimensions	130 x 54 x 130 mm
Weight	470 g
Connections	Inputs: 1 x 6.3 mm stereo jack L/R, analogue 1 x 3-pole XLR L/R, analogue

- Metal housing
- Power is provided via enclosed plug-in power supply



FLY-16T

Order No. 0259580

16-channel wireless PA audio transmitter, with UHF PLL technology.

- For analogue wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Indication for channel and battery status
- Supplied with USB cable

Model	FLY-16T
Description	16-channel wireless PA audio transmitter
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
THD	0.3%
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Operating range	approx. 90 m
Power supply transmitter	1 x 1.5 V batt. AA size, = 5 V/150 mA via micro USB jack
Dimensions transmitter	22 x 23 x 116 mm
Weight transmitter	54 g
Connections transmitter	3-pole XLR jack



FLY-16R

Order No. 0259570

16-channel wireless PA audio receiver, with UHF PLL technology.

- For analogue wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Multiple receivers FLY-16R can be operated via one transmitter FLY-16T

Model	FLY-16R
Description	16-channel wireless PA audio receiver
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
THD	0.3%
Admiss. ambient temp.	0-40 °C
Power supply receiver	1 x 1.5 V batt. AA size, = 5 V/150 mA via micro USB jack
Dimensions receiver	22 x 23 x 102 mm
Weight receiver	25 g
Connections receiver	3-pole XLR plug

- Indication for channel and battery status
- Supplied with USB cable



FLY-16SET

Order No. 0259854

16-channel wireless PA audio transmission set, with UHF PLL technology.

- Consisting of 16-channel wireless PA audio transmitter FLY-16T and 16-channel wireless PA audio receiver FLY-16R
- For analogue wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Audio transmission range: 30-17,000 Hz
- Compact size
- For further specifications, please refer to individual items



There are restrictions or requirements in the EU!

Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!