

Microphones

Wireless Transmission

TXS-606

Order No. 0253510

Multifrequency receiver unit, with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) in 10 groups with 100 frequencies each
- ACT function for transmitting selected frequency to pocket transmitter TXS-606LT or hand-held microphone TXS-606HT via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)

Model	TXS-606
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	350 mV/600 Ω (jack) 25 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	212 x 45 x 180 mm
Weight receiver	930 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

- Volume and squelch controls



TXS-626

Order No. 0253520



2-channel multifrequency receiver unit, with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) for each channel (10 groups with 100 frequencies each)
- ACT function for transmitting selected frequency to pocket transmitter TXS-606HSE/2, tie clip microphone transmitter TXS-606LT/2, desktop microphone transmitter TXS-606DT/2 or hand-held microphone TXS-606HT/2 via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)

Model	TXS-626
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	350 mV/600 Ω (jack) 25 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	482 x 45 x 195 mm
Weight receiver	1.8 kg
Connections receiver	2 x XLR, bal., 1 x 6.3 mm jack, unbal.

- Volume and squelch controls for each channel



TXS-646

Order No. 0253530



4-channel multifrequency receiver unit, with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) for each channel (10 groups with 100 channels each)
- ACT function for transmitting selected frequency to pocket transmitter TXS-606HSE/2, tie clip microphone transmitter TXS-606LT/2, desktop microphone transmitter TXS-606DT/2 or hand-held microphone TXS-606HT/2 via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)

Model	TXS-646
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	350 mV/600 Ω (jack) 25 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	482 x 45 x 310 mm
Weight receiver	2.9 kg
Connections receiver	4 x XLR, bal., 1 x 6.3 mm jack, unbal.

- Volume and squelch controls for each channel



TXS-686

Order No. 0257320



8-channel multifrequency receiver unit, with UHF PLL technology.

- 1,000 selectable UHF frequencies (672.000-696.975 MHz) for each channel (10 groups with 100 channels each)
- ACT function for transmitting selected frequency to pocket transmitter TXS-606HSE/2, tie clip microphone transmitter TXS-606LT/2, desktop microphone transmitter TXS-606DT/2 or hand-held microphone TXS-606HT/2 via infrared signal
- Auto-scan
- True diversity system with removable antennas (BNC connection)

Model	TXS-686
Carrier frequency range	672.000-696.975 MHz
Audio frequency range	30-18,000 Hz
THD	< 0.5%
Dynamic range	100 dB
RF S/N ratio	105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	350 mV/600 Ω (jack) 25 mV/600 Ω (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Dimensions receiver	482 x 90 x 310 mm
Weight receiver	4.4 kg
Connections receiver	8 x XLR, bal., 1 x 6.3 mm jack, unbal.

- Volume and squelch controls for each channel

