

### TXS-606HT/2

Order No. 1000185

**Hand-held microphone with integrated multi-frequency transmitter**, with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/ low: 2.5 mW)

Model	TXS-606HT/2
Polar pattern	cardioid
System	dynamic
Carrier frequency range	672.000-691.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Dimensions	Ø 51 mm x 265 mm
Weight	312 g

- LCD for indicating group/channel, audio level and battery status



### TXS-606HSE/2

Order No. 1000184

**Multifrequency pocket transmitter**, with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Suitable for combination with headband/earband microphones and tie clip microphones with 3-pole mini XLR connector

Model	TXS-606HSE/2
Carrier frequency range	672.000-691.975 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 8 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	61 x 106 x 27 mm
Weight transmitter	80 g
Connections transmitter	1 x 3-pole mini XLR



### TXS-606LT/2

Order No. 1000186

**Multifrequency tie clip microphone transmitter**, with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Tie clip microphone with latchable 3.5 mm plug

Model	TXS-606LT/2
Carrier frequency range	672.000-691.975 MHz
Audio frequency range	30-18,000 Hz
Operating time	> 8 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size
Dimensions transmitter	61 x 106 x 27 mm
Weight transmitter	96 g
Connections transmitter	1 x 3.5 mm jack



### TXS-606DT/2

Order No. 1000183

**Wireless desktop microphone with integrated multifrequency transmitter**, with UHF PLL technology.

- Electret microphone cartridge, cardioid polar pattern
- 350 mm gooseneck, removable
- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Switchable transmitting power (high: 25 mW/ low: 2.5 mW)

Model	TXS-606DT/2
Polar pattern	cardioid
System	electret
Carrier frequency range	672.000-691.975 MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 8 h
Audio frequency range	30-18,000 Hz
Dimensions	120 x 65 x 178 mm (w/o gooseneck)
Weight	1.2 kg

- Adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status



**There are restrictions or requirements in the EU!**

**Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!**