

### TXS-865HT

Order No. 0255310

**Dynamic hand-held UHF PLL transmitter**, with REMOSET technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 124 selectable channels in 6 channel groups (506-542 MHz)
- Adjustable sensitivity (12 dB to -18 dB)
- Backlit LCD for indicating channel and battery status
- Switchable transmitting power: 10 mW/50 mW (EIRP)
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Supplied with robust transport case and stand clamp

Model	TXS-865HT
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10 mW/50 mW, switchable
Power supply	2 x batt. AA size, alkaline
Operating time	> 25 h
Audio frequency range	50-16,000 Hz
Dimensions	Ø 50 mm x 250 mm
Weight	350 g



### TXS-865HSE

Order No. 0255300

**UHF PLL pocket transmitter**, with REMOSET technology.

- Suitable for combination with headband microphone or earband microphone with 3-pole mini XLR connector
- 124 selectable channels in 6 channel groups
- Adjustable sensitivity (12 dB to -18 dB)
- Selectable attenuation (0 dB/-6 dB/-20 dB)
- Lock function
- Backlit LCD for indicating channel and battery status

Model	TXS-865HSE
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
Operating time	> 25 h
Admiss. ambient temp.	0-40 °C
Transmitting power	10 mW
Power supply transmitter	2 x batt. AA size, alkaline
Dimensions transmitter	68 x 172 x 21 mm
Weight transmitter	77 g
Connections transmitter	1 x 3-pole mini XLR



### TXS-855

Order No. 0255280

**Single-channel diversity UHF PLL receiver**, with REMOSET technology.

- 124 selectable channels in 6 channel groups
- Parallel operation of up to 20 channels
- Diversity system with removable antennas
- Integrated scan function
- Pilot tone squelch and noise squelch

Model	TXS-855
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 42 x 195 mm
Weight receiver	525 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, bal.



### TXS-865

Order No. 0255290



**2-channel diversity UHF PLL receiver**, with REMOSET technology.

- 124 selectable channels in 6 channel groups (506-542 MHz)
- Parallel operation of up to 20 channels
- Diversity system with removable antennas (BNC connection)
- Integrated scan function
- Pilot tone squelch and noise squelch
- Attenuator with 2-way switching

Model	TXS-865
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	420 x 54 x 230 mm
Weight receiver	2 kg
Connections receiver	2 x XLR, bal., 1 x 6.3 mm jack, bal.



**There are restrictions or requirements in the EU!**

**Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!**