

## ATT100

Order No. 0259864

### Tour guide transmitter

- 10+10 pre-programmed channels, channels 1-10 are transmitting with low power (operating range: approx. 200 m), channels 11-20 are transmitting with increased power (PMR446 standard: high operating range of up to 2 km)
- High battery capacity for continuous announcements of up to 6 hours
- 3 different operating modes can be selected:
  - Continuous transmission
  - Voice control
  - Control via push-to-talk buttons (PTT)

- Matching the tour guide receiver ATR200
- Fully programmable (depending on the application)
- Supplied with belt clip, lanyard

**Licence-free, please refer to instruction manual on MONACOR's website.**



## ATR200

Order No. 0259863

2x

### Tour guide receivers, set of 2.

- 20 pre-programmed channels
- Extra small and ultra-light (approx. 40 g)
- Channel coding
- Anti-noise system (no cracks or loud noise after end of transmission)
- Foolproof operation via 3 buttons only
- Large multifunction LED display (operation, charging, receiving)
- Lock function by means of sliding switch
- Micro USB jack for charging (also via PC)
- Matching the tour guide transmitter ATT100

- Connection for supplied earphones
- Belt clip
- USB charger for simultaneously charging 2 receivers ATR200 in less than 6 hours

**Licence-free, please refer to the instruction manual on MONACOR's website.**



## COHS

Order No. 0259867

### Universal headset for motorcycle helmets, with 2 microphones for full face helmets and jet helmets.

- For connection to the basic set BHS300N
- Cable-connected microphone and gooseneck microphone for mounting to full face helmets or jet/modular helmets

- Increased cable diameter (1.75 mm) and improved cable bending protection
- Waterproof plug with connection cable for basic set



## G-7SET

Order No. 0250760



### Pair of professional dual-band transceivers, case set,

consisting of 2 transceivers with belt clip, 2 clip-on mics with earphones, charger for 2 transceivers, 2 rech. battery packs.

- 8 PMR channels 446 MHz
- 69 LPD channels 433 MHz
- Boost function for a wide operating range
- High-performance rech. batteries for high operational availability
- Manual transmit mode (PTT) or hands-free voice-activated transmit mode (VOX)
- Monitoring function
- Automatic squelch
- Channel scan mode (SCAN)
- CTCSS tones

Model	G-7SET
Carrier frequency range	446.00625-446.09375 MHz (PMR) 433.075-434.775 MHz (LPD)
Admiss. ambient temp.	-20 °C to +55 °C
Power supply	4 x rech. battery AA size, 800 mAh
Dimensions	58 x 195 x 34 mm
Total weight	1.203 kg
Connections	2.5 mm jack (microphone) 3.5 mm jack (speaker)
Transmitting power	500 mW
Operating range	≤ 5,000 m

- Dual watch
- Vibracall function
- Key lock
- Backlit LCD
- Supplied in a robust hard-sided case

**Licence-free, please refer to instruction manual on the MONACOR website.**

