

FLAT-M100

Order No. 0259590



Active PA stage monitor speaker system, 200 W

- Flat and very compact full range system
- Fitted with 2 x 10 cm (FaitalPRO, 2 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 116 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

| Model | FLAT-M100 |
|--------------------|--|
| Total output power | 200 W |
| Power rating (RMS) | 100 W |
| Frequency range | 90-20,000 Hz |
| Input signal | 16 mV/28 kΩ (line, bal), 5 mV/20 kΩ (mic, bal) |
| SPL | 97 dB/W/m |
| Mounting device | 2 x M10 threaded insert, 2 x M6 threaded insert |
| Power supply | ~ 230 V/50 Hz/175 VA |
| Dimensions | 265 x 120 x 192,5 mm |
| Weight | 2.4 kg |
| Inputs | 1 x comb. XLR/6.3 mm (line/mic) |
| Outputs | 1 x XLR link out |



FLAT-M100BAG

Order No. 0179030

Transport and protective bag

- Suitable for active PA stage monitor speaker system FLAT-M100
- Black, partly padded nylon version with zip fastener
- Carrying handle, rubber feet and lateral cable bag



FLAT-M200

Order No. 0259876



Active PA stage monitor speaker system, 300 W

- Flat and very compact full range system
- Fitted with 4 x 10 cm (FaitalPRO, 4 x 4") full range speaker with neodymium magnets
- Class D amplifier system
- Sound pressure at nominal power: 122 dB
- Indication of signal and limiter
- Volume control and tone control
- Balanced line/mic input and feed-through output
- High-quality multiplex wooden cabinet with protective metal grille
- 2 x M10 and 2 x M6 threaded inserts for stand adapter or mounting device
- Supplied with clamp for mounting, e.g. onto a microphone stand

| Model | FLAT-M200 |
|--------------------|--|
| Total output power | 300 W |
| Power rating (RMS) | 200 W |
| Frequency range | 70-20,000 Hz |
| Input signal | 25 mV/28 kΩ (line, bal), 6 mV/20 kΩ (mic, bal) |
| SPL | 98 dB/W/m |
| Mounting device | 2 x M10 threaded insert, 2 x M6 threaded insert |
| Power supply | ~ 230 V/50 Hz/356 VA |
| Dimensions | 320 x 150 x 250 mm |
| Weight | 4.11 kg |
| Inputs | 1 x comb. XLR/6.3 mm (line/mic) |
| Outputs | 1 x XLR link out |



FLAT-M200BAG

Order No. 0179260

Transport and protective bag

- Suitable for active PA stage monitor speaker system FLAT-M200
- Black, partly padded nylon version with zip fastener
- Carrying handle, rubber feet and lateral cable bag

