

Components

Stage and Audio Accessories

MR-162DESK

Order No. 0252180



Professional rolling case for 482 mm (19") devices, with 2 integrated desks.

- 9 RU mounting facility for 482 mm top-operated devices (mixers or similar), upward tilting rack rails with click-stop hinges
- 16 RU mounting zone for devices which require horizontal mounting
- Suitable for devices with a max. depth of 480 mm
- Front part and rear part with integrated folding feet (desk feature), effective surface: approx. 920 x 525 mm each, height: approx. 760 mm each

- 9 mm multiplex wood, moisture repellent, black, plastic-laminated (slightly structured)
- Robust bottom plate, 13 mm thick
- Aluminium profile edges
- Chrome-plated ball protection corners and closing angles
- 100 mm castors, 2 of which are provided with locking brakes
- Butterfly locks
- 2 recessed drop handles at each side ensure safe and convenient handling
- Inside dimensions: 500 x 715 x 520 mm



MR-106PC

Order No. 0250190



Flight case, with integrated laptop rack.

- 6 RU: Vertical profile rails for inserting 482 mm (19") devices. Suitable for devices with a maximum depth of 480 mm
- 8 RU: Horizontal and slightly upward tilted mounting rails for 482 mm (19") top-operated devices, e.g. mixers
- Sliding top part with non-slip surface for laptops
- 9 mm plywood, black laminated
- Aluminium profile edges

- Chrome-plated ball corners, reinforcing angles and connectors
- Butterfly locks and recessed drop handles
- Rear service cover with cable outlet
- Inside dimensions: 515 x 390 x 590 mm
- Outside dimensions: 570 x 445 x 630 mm
- Weight: 20 kg
- Supplied with 32 cage nuts

Supplied w/o devices.



MR-919DJ

Order No. 0244710



Flight case, 9 RU, for 482 mm (19") top-operated devices, e.g. mixers. Mounting rails with a fixed inclination angle of approx. 13°, thus the mounting depth varies between 100 and 185 mm.

- Plywood, black laminated
- Aluminium profile edges
- Chrome-plated ball corners, reinforcing angles
- Butterfly locks and recessed drop handles
- Particularly suitable for variable installation of devices

using castle nuts M6 x 7 mm; aluminium rails with non-slipping feature (guiding rubber prevents slipping of the castle nuts, thus easy mounting)

- Dimensions: 527 x 230 x 485 mm
- Weight: 8.2 kg
- Supplied with 4 castle nuts

Supplied w/o devices.



RCS-92/SW

Order No. 0111410



- Rack-mount power strip**, with 9 earthed sockets.
- Sockets turned by 45°
 - Black aluminium housing
 - Removable mounting brackets
 - 2 m connection cable with earthed plug

- Cable specification: H05VV-F3G x 1.5 mm², 3,600 VA max.
- Dimensions: 482 x 44 x 45 mm, 1 RU

RCS-18

Order No. 0111200



- Rack-mount power strip**, with 8 earthed sockets and overvoltage protection.
- Child safety sockets
 - Sockets turned by 45°
 - Illuminated main switch
 - Black plastic housing

- 1 m connection cable with earthed plug, cable inlet can be turned by 90° via flexible joint
- Cable specification: H05VV-F3G x 1.5 mm², 3,600 VA max.
- Dimensions: 482 x 44 x 60 mm, 1 RU

RCS-85/SW

Order No. 0111850



- Rack-mount power strip**, with an illuminated main switch on the front panel and 8 earthed sockets on the rear panel.
- Sockets turned by 45°
 - Removable mounting brackets to allow for reversed mounting

- Black aluminium housing
- 2 m connection cable with earthed plug
- Cable specification: H05VV-F3G x 1.5 mm², 3,600 VA max.
- Dimensions: 482 x 44 x 52 mm, 1 RU

MCS-180

Order No. 0050002



- Rack-mount power strip**, with 8 earthed sockets.
- Sockets can be switched individually via illuminated switches
 - Black sheet steel housing
 - 1.8 m connection cable with earthed plug

- Cable specification: H05VV-F3G x 1.5 mm², 3,600 VA max.
- Dimensions: 482 x 89 x 110 mm, 2 RU