

ESP-250/WS

Order No. 0162780



ESP-230/WS

Order No. 0190010



ESP-215/WS

Order No. 0199990



PA speaker systems, in a weatherproof white plastic cabinet with aluminium protective grille.

- 100 V transmission technology
- Hose-proof
- Switchable to 8 Ω operation
- 5 power taps, 8 Ω connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket



Model	ESP-250/WS	ESP-230/WS	ESP-215/WS
Total power rating	100 W	100 W	60 W
Power rating (RMS)	50/40/30/20/10 W (100 V) 50 W (8 Ω)	30/20/10/5/2.5 W (100 V) 50 W (8 Ω)	15/10/5/2.5/1.5 W (100 V) 30 W (8 Ω)
Impedance	8 Ω	8 Ω	8 Ω
Frequency range	80-20,000 Hz	80-20,000 Hz	100-20,000 Hz
SPL	92 dB/W/m	92 dB/W/m	87 dB/W/m
Protection class	IP65	IP65	IP65
Admiss. ambient temp.	-20 °C to +50 °C	-20 °C to +50 °C	-20 °C to +50 °C
Dimensions	157 x 260 x 170 mm	157 x 260 x 170 mm	98 x 195 x 105 mm
Weight	2.4 kg	1.8 kg	0.85 kg

ESP-232/SW

Order No. 0162600



ESP-232/WS

Order No. 0162610



Weatherproof 2-way PA wall-mount speaker systems

- 100 V PA speaker system with an excellent sound
- 13 cm polypropylene bass-midrange speaker and tweeter
- 4 power taps
- Power selector switch with 8 Ω operating position

Model	ESP-232/SW	ESP-232/WS
Total power rating	50 W	50 W
Power rating (RMS)	30/20/10/5 W (100 V) 25 W (8 Ω)	30/20/10/5 W (100 V) 25 W (8 Ω)
Impedance	8 Ω	8 Ω
Frequency range	75-20,000 Hz	75-20,000 Hz
Number of built-in speakers	2	2
SPL	89 dB	89 dB
Protection class	IP55	IP55
Admiss. ambient temp.	-20 °C to +50 °C	-20 °C to +50 °C
Dimensions	160 x 260 x 180 mm	160 x 260 x 180 mm
Weight	2.3 kg	2.3 kg



EUL-26/SW

Order No. 0163280



EUL-26/WS

Order No. 0163290



Pair of miniature PA speaker systems

- Speakers for general applications, very small dimensions, 100 V transmission technology
- Can also be connected at 8 Ω
- 6.5 cm (2.5") full range speaker
- Good sound characteristics and speech intelligibility
- Turnable, for pivoting and tilting
- An additional subwoofer system is recommended for complementing the low-frequency music reproduction (e.g. EUL-2SUB/SW, SOUND-100SUB)

Model	EUL-26/SW, EUL-26/WS
Total power rating	20 W
Power rating (RMS)	6 W (100 V) 10 W (8 Ω)
Frequency range	150-20,000 Hz
SPL	88 dB/W/m
Dimensions	90 x 90 x 115 mm
Weight	0.65 kg

