

Speakers

PA Systems

MOVE-12PMK2

Order No. 1000227



Professional PA speaker system, 350 W, 8 Ω

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 30 cm (128", FaisalPro 12PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out

Model	MOVE-12PMK2
Total power rating	700 W
Power rating (RMS)	350 W
Impedance	8 Ω
SPL	98 dB/W/m
Dimensions	350 x 620 x 385 mm
Weight	16.4 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par.out

- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3



MOVE-10PMK2

Order No. 1000226



Professional PA speaker system, 350 W, 8 Ω

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 25 cm (10", FaisalPro 10PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out

Model	MOVE-10PMK2
Total power rating	700 W
Power rating (RMS)	350 W
Impedance	8 Ω
Frequency range	55-20,000 Hz
SPL	96 dB/W/m
Dimensions	320 x 545 x 350 mm
Weight	13.9 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par.out

- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3



MOVE-08PMK2

Order No. 1000225



Professional PA speaker system, 250 W, 8 Ω

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 20 cm (8", FaisalPro 8PR200) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out

Model	MOVE-08PMK2
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 Ω
Frequency range	65-20,000 Hz
SPL	95 dB/W/m
Dimensions	290 x 490 x 315 mm
Weight	12.6 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par.out

- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3



MOVE-12/BAG

Order No. 1000210

MOVE-10/BAG

Order No. 1000207

MOVE-08/BAG

Order No. 1000204

Protective covers for speaker systems

MOVE-12/BAG for PA speaker system MOVE-12PMK2

MOVE-10/BAG for PA speaker system MOVE-10PMK2

MOVE-08/BAG for PA speaker system MOVE-08PMK2

- Outer material made of robust, black synthetic cloth
- Openings for handles

