

Speakers PA Systems

EUL-2/SW


Order No. 0174450



PA speaker system, 100 V transmission technology

- High-quality cabinet with durable PU coating
- 20 cm (2 x 8") double bass speaker of high power capability and a dyn. 25 mm (1") horn tweeter
- Well-balanced and dynamic sound for speech and music applications
- SPEAKON connection, rotary switch for power selection, stand sleeve
- A subwoofer support is useful for bass reproductions of high requirements (e.g. with EUL-2SUB/SW)
- This speaker can be integrated into any existing or new 100 V system by simply connecting it in parallel, as long as the amplifier features the respective power reserves

Matching adapter piece for speaker system PAST-28/SW is available at option.



Model	EUL-2/SW
Power rating (RMS)	50/37.5/25/12.5 W
Frequency range	70-19,000 Hz
SPL	95 dB/W/m
Dimensions	320 x 485 x 250 mm
Weight	8.7 kg
Inputs	1 x SPEAKON

EUL-2SUB/SW


Order No. 0174460



Subwoofer in 100 V line technique

- High-quality cabinet with durable PU coating
- 30 cm (12") bass speaker for a deep and dynamic bass reproduction
- SPEAKON connections (input and sat out/par. out)
- The design and high efficiency perfectly match the EUL-2/SW, but it is also suitable as an addition to many other 100 V systems
- Built-in crossover network (low-pass) allows for an almost unlocatable bass
- Please ensure that the 100 V amplifier provides sufficient power capabilities!

Matching adapter piece for speaker system PAST-28/SW is available at option.



Model	EUL-2SUB/SW
Power rating (RMS)	120/90/60/30 W
Frequency range	38-250 Hz
SPL	95 dB/W/m
Dimensions	420 x 430 x 445 mm
Weight	18.2 kg
Inputs	1 x SPEAKON IN
Outputs	1 x SPEAKON par. out/sat out