

## IT-100RTW

Order No. 0163340



### Weatherproof horn speaker (music horn), 2-way technology

- 100 V transmission technology with very high tapping power
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 13 cm bass-midrange speaker and 25 mm (1") horn
- Due to round design, consistent radiation pattern in the required area, e.g. ceiling suspension in halls
- Robust plastic housing
- Supplied with mounting bracket and screws made of stainless steel

Model	IT-100RTW
Power rating (RMS)	30/15/7.5/3.75 W
Frequency range	150-20,000 Hz
SPL	101 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 300 mm x 360 mm
Weight	4.4 kg



## IT-60

Order No. 0162990



### Weatherproof horn speaker, with high power capability.

- 100 V transmission technology
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Light grey ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with stainless steel mounting bracket
- Integrated ceramic connection terminal with thermal fuse
- 4 power taps

Model	IT-60
Power rating (RMS)	60/30/15/7.5 W
Frequency range	230-9,000 Hz
SPL	110 dB/W/m
Beam angle	H: 80°/V: 30°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 305 mm x 385 mm
Weight	4 kg



## IT-40

Order No. 0161360



### Weatherproof horn speaker

- 100 V transmission technology
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel
- 5-step power selector switch

Model	IT-40
Power rating (RMS)	40/30/20/10/5 W
Frequency range	180-7,000 Hz
SPL	113 dB/W/m
Beam angle	H: 100°/V: 45°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	400 x 200 x 420 mm
Weight	3.66 kg

