

IT-130

Order No. 0161710



Weatherproof horn speaker

- 100 V transmission technology
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-130
Power rating (RMS)	30/15/10/5/3/1 W
Frequency range	250-16,000 Hz
SPL	109 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	290 x 215 x 260 mm
Weight	1.6 kg



IT-115

Order No. 0161700



Weatherproof horn speaker

- 100 V transmission technology
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-115
Power rating (RMS)	15/10/5/3/1 W
Frequency range	280-12,500 Hz
SPL	108 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	225 x 160 x 235 mm
Weight	1.3 kg



IT-110

Order No. 0161690



Horn speaker

- 100 V transmission technology
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Power selector switch
- For open-air events, industrial use, in workshops

Model	IT-110
Power rating (RMS)	10/5/3/1 W
Frequency range	315-12,500 Hz
SPL	105 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	175 x 130 x 185 mm
Weight	1.1 kg



NR-254KS

Order No. 0162480



Weatherproof horn speaker

- 4 Ω speaker system
- IP66 tested, protected against powerful water jets
- Especially suitable for voice transmissions
- Robust plastic housing of compact size
- 2-wire connection cable, length: 60 cm
- Mounting bracket and screws made of stainless steel

Model	NR-254KS
Total power rating	25 W
Power rating (RMS)	12 W
Frequency range	800-8,000 Hz
SPL	107 dB/W/m
Beam angle	H: 90°/V: 90°
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	106 x 106 x 88 mm
Weight	1.08 kg

