

Speakers

Horn Speakers

KU-916T

Order No. 0161610



Weatherproof horn driver

- 100 V transmission technology
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1 3/8") mounting flange
- 60 cm connection cable

Model	KU-916T
Power rating (RMS)	60/50/40/30/20/10 W
Frequency range	160-7,000 Hz
SPL	113 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 150 mm x 158 mm
Weight	2.75 kg



KU-616T

Order No. 0160710



Weatherproof horn driver

- 100 V transmission technology
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1 3/8") mounting flange
- 55 cm connection cable

Model	KU-616T
Power rating (RMS)	40/30/20/10/5 W
Frequency range	160-6,500 Hz
SPL	112 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 150 mm x 136 mm
Weight	2.2 kg



KU-516

Order No. 0160700



Weatherproof horn driver

- Diecast version, IP66
- Protected against powerful water jets
- 3.5 cm (1 3/8") mounting flange

Model	KU-516
Total power rating	75 W
Power rating (RMS)	50 W
Frequency range	160-6,500 Hz
SPL	113 dB/W/m
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 126 mm x 100 mm
Weight	1.9 kg

