

EDL-416EN/WS

Order No. 0163420



Moisture-proof PA ball speaker, with EN 54-24 certification, 1438-CPR-0535.

- 100 V transmission technology
- White ABS housing (UL 94HB), UV-resistant and weatherproof
- Moisture-proof speaker cone
- Supplied with 450 cm connection cable and canopy
- Ceramic connection terminal, thermal fuse

Model	EDL-416EN/WS
Power rating (RMS)	16/8/4 W
Frequency range	130-18,000 Hz
SPL	89.9 dB/W/m
Beam angle	196° (1 kHz) 132° (2 kHz) 170° (4 kHz)
Admiss. ambient temp.	-20 °C to +80 °C
Dimensions	Ø 185 mm x 157 mm
Weight	1.6 kg



EDL-412/SW

Order No. 1000620



EDL-412/WS

Order No. 0161860



Weatherproof PA ball speakers

- 100 V transmission technology or 8 Ω operation
- Black (SW) or white (WS) ABS housing, self-extinguishing, complies with standard UL 94V-0
- Supplied with 480 cm connection cable with canopy

Model	EDL-412/SW, EDL-412/WS
Power rating (RMS)	10/5/2.5 W
Frequency range	160-20,000 Hz
SPL	92 dB/W/m
Dimensions	Ø 184 mm
Weight	1.65 kg



RL-1ENABDS

Order No. 0163690



PA A/B sound projector for wall mounting, with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V transmission technology
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Model	RL-1ENABDS
Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-20,000 Hz
SPL	93 dB/W/m
Beam angle	130°
Dimensions	Ø 144 mm x 210 mm
Weight	2.3 kg



RL-1EN

Order No. 0163680



PA sound projector for wall mounting, with EN 54-24 certification.

- 100 V transmission technology
- 13 cm full range speaker
- 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Model	RL-1EN
Power rating (RMS)	6/3/1.5 W
Frequency range	80-20,000 Hz
SPL	93 dB/W/m
Beam angle	130°
Dimensions	Ø 144 mm x 210 mm
Weight	1.9 kg

