

ADP-DAI-1X0

Order No. 0259650



Dante® AVIO analogue input adapter (1-channel)

- For connecting analogue audio line level devices (e.g. mixer) to a Dante® audio network
- Adjustable signal level: +24/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 20 kΩ (bal.), 10 kΩ (unbal.)
- Dynamic range: > 100 dB

- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR inline jack

ADP-DAI-2X0

Order No. 0259660



Dante® AVIO analogue input adapter (2-channel)

- For connecting analogue audio line level devices (e.g. mixer) to a Dante® audio network
- Adjustable signal level: +24/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 20 kΩ (bal.), 10 kΩ (unbal.)
- Dynamic range: > 100 dB

- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR inline jack

ADP-DAO-0X1

Order No. 0259670



Dante® analogue output adapter (1-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 kΩ (bal.), 75 kΩ (unbal.)
- Dynamic range: > 100 dB

- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR plug

ADP-DAO-0X2

Order No. 0259680



Dante® analogue output adapter (2-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 kΩ (bal.), 75 kΩ (unbal.)
- Dynamic range: > 100 dB

- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR plug

ADP-USB-2X2

Order No. 0259690



Dante® AVIO USB adapter

- For connecting a computer to a Dante® audio network
- 2-channel recording/reproduction
- Sampling rate: 48 kHz, 24 bits
- Compatible with Windows, Mac OS, iOS and Android devices, no drivers required
- Connections: 1 x RJ45, 1 x USB Type-A

ADP-AES3-2X2

Order No. 0259640



Dante® AVIO AES3/EBU adapter

- For connecting analogue devices with AES3/EBU interface to a Dante® audio network
- Impedance: 110 Ω (bal.)
- S/N ratio: > 135 dB
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 1 x XLR plug, 1 x XLR inline jack

ADP-BT-AU-2X1

Order No. 1000801



Dante® AVIO Bluetooth adapter

- For connection a Bluetooth device to a Dante® audio network
- 2-channel recording/playback
- Sampling rate: 48 kHz, 24 bits
- Bluetooth Version 5.0 A2DP (AptX, AAC) und HFP
- Compatible with Windows, Mac OS, iOS and Android devices, no driver required
- Connections: 1 x RJ45

ADP-USBC-2X2

Order No. 1000156



Dante® AVIO USB adapter

- For connecting a computer or a mobile device to a Dante® audio network
- 2-channel recording/playback
- Sampling rate: 48 kHz, 24 bits
- Compatible with Windows, Mac OS, iOS and Android devices, no driver required
- Connections: 1 x RJ45, 1 x USB Type-C™