

Voice Alarm Systems

EN 54 Speakers

EDL-530EN/SW

Order No. 1000261



EDL-530EN/WS

Order No. 1000262



High-quality PA pendant speakers, with EN 54-24 certification.

- 100 V transmission technology or 8 Ω operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

Model	EDL-530EN/SW, EDL-530EN/WS
Power rating (RMS)	30/15/7.5/3.8 W
Impedance	8 Ω
Frequency range	65-20,000 Hz
SPL	90 dB/W/m
Housing material	ABS
Dimensions	Ø 195 mm x 250 mm
Weight	2.26 kg
Inputs	plug-in screw terminal



EDL-416EN/WS

Order No. 0163420



Moisture-proof PA ball speaker, with EN 54-24 certification, 1438-CPR-0535.

- 100 V transmission technology
- White ABS housing (UL 94HB), UV-resistant and weatherproof
- Moisture-proof speaker cone
- Supplied with 450 cm connection cable and canopy
- Ceramic connection terminal, thermal fuse

Model	EDL-416EN/WS
Power rating (RMS)	16/8/4 W
Frequency range	130-18,000 Hz
SPL	89.9 dB/W/m
Beam angle	196° (1 kHz) 132° (2 kHz) 170° (4 kHz)
Protection class	IP35
Admiss. ambient temp.	-20 °C to +80 °C
Dimensions	Ø 185 mm x 157 mm
Weight	1.6 kg



ESP-1000AB

Order No. 0163670



PA A/B wall speaker, with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V transmission technology
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille
- Supplied with aluminium mounting bracket, screws and wall plugs

Model	ESP-1000AB
Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-20,000 Hz
SPL	92 dB/W/m
Beam angle	160°
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	Ø 220 mm x 100 mm
Weight	1.98 kg

