

### ESP-70/WS

Order No. 0162120



#### PA wall speaker

- 100 V transmission technology
- 5-step rotary switch for 10/6/4/2 W/off
- Rotary switch can be replaced with a cover plate to avoid accidental changing of the power selection
- Emergency priority relay
- White wooden cabinet with protective metal grille
- Easy wall mounting via supporting plate
- Ball-proof according to DIN 18032, Part 3

Model	ESP-70/WS
Power rating (RMS)	10/6/4/2 W
Frequency range	95-19,000 Hz
Dimensions	300 x 200 x 90 mm
Weight	2.3 kg



### ESP-60/WS

Order No. 0161110



#### PA wall speaker

- 100 V transmission technology via audio transformer with 4 power taps
- White wooden cabinet, without rear panel, foam front cover
- Supplied with mounting screws

Model	ESP-60/WS
Power rating (RMS)	6/4/2/1 W
Frequency range	60-8,000 Hz
Dimensions	300 x 200 x 90 mm
Weight	1.8 kg



### ESP-1000AB

Order No. 0163670



**PA A/B wall speaker**, with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V transmission technology
- 2 x 10 cm full range speaker
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Plastic cabinet with open rear panel with protective metal front grille

Model	ESP-1000AB
Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-20,000 Hz
SPL	92 dB/W/m
Beam angle	160°
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	Ø 220 mm x 100 mm
Weight	1.98 kg

- Supplied with aluminium mounting bracket, screws and wall plugs



### ESP-90/WS

Order No. 0162680



#### PA wall speaker

- 100 V transmission technology via audio transformer with 3 power taps
- White plastic housing (surface-mount version with open rear panel) with protective metal grille
- Supplied with mounting accessories

Model	ESP-90/WS
Power rating (RMS)	6/3/1.5 W
Frequency range	80-19,000 Hz
Dimensions	Ø 168 mm x 72 mm
Weight	600 g

