

Speakers

Wall and Ceiling Speakers

ESP-360/WS

Order No. 0161900



PA wall speaker

- 100 V transmission technology via audio transformer with 2 power taps
- Full range speaker with dual cone
- White plastic cabinet
- Curved cabinet for a perfect radiation angle

Model	ESP-360/WS
Power rating (RMS)	6/3 W
Frequency range	130-15,000 Hz
Dimensions	185 x 255 x 123 mm
Weight	1.1 kg
Inputs	power taps



ESP-134/WS

Order No. 1000264



PA wall speaker

- 100 V transmission technology via audio transformer with 3 W and 6 W power taps or 4 Ω operation (20 W)
- 2-way system with neodymium bass-midrange speaker and dome tweeter
- White plastic cabinet with protective metal grille
- Super slimline design for unobtrusive wall mounting

Model	ESP-134/WS
Power rating (RMS)	6/3 W (100 V) 20 W (4 Ω)
Power rating (RMS)	6/3 W
Impedance	4 Ω
Frequency range	80-18,000 Hz
SPL	91 dB/W/m
Beam angle	H: 100°/V: 60°
Dimensions	185 x 275 x 38 mm
Weight	1.25 kg
Inputs	spring-loaded terminal



ESP-80/WS

Order No. 0162380



PA wall speaker, vandal-resistant.

- 100 V transmission technology via audio transformer with 4 power taps
- Full range speaker with a good voice reproduction, suitable for background music
- Very robust 2-piece metal housing

Model	ESP-80/WS
Power rating (RMS)	6/3/1,5/0.75 W
Frequency range	250-10,000 Hz
Dimensions	170 x 170 x 63 mm
Weight	1.5 kg

